

Contents

Notation	IX
Zusammenfassung	XV
Abstract	XXIII
1 Introduction	1
1.1 Autothermal reactor concepts for endothermic syntheses	1
1.2 Motivation and content overview	4
2 Autothermal Reverse-Flow Reformer	7
2.1 Methane steam reforming	7
2.1.1 Reaction system	8
2.2 Energy efficient reactor concepts for MSR - State of the art	10
2.3 Reverse-flow reformer	12
2.3.1 Fundamentals of the operation principle	13
2.3.2 Short cut method for reactor design	20
2.3.3 Experimental validation and technical limitations	22
2.4 Summary	24
3 Flameless combustion for heat supply in a packed bed	25
3.1 Flameless Oxidation (FLOX) and its conventional applications	25
3.2 Flameless combustion concept in a packed-bed reactor	27
3.3 Suitability analysis and combustion chamber development	30
3.3.1 CFD-Simulations	31
3.3.2 Tracer Methods	34
3.4 Combustion experiments in a single chamber reactor	41
3.4.1 Stationary operation	41
3.4.2 Ignition and dynamic behaviour	48
3.4.3 Understoichiometric combustion	57
3.5 Summary	61

4	Reheating strategy	63
4.1	Stoichiometric combustion concept	63
4.2	Design constraints and combustion chamber operation range	65
4.2.1	Operation constraints	65
4.2.2	Chamber performance within the design operation range	68
4.3	Systematic combustion chamber design based on CFD	74
4.3.1	Performance indicators	75
4.3.2	Simulation results - Correlation with performance indicators	78
4.3.3	Reduced models for the combustion chamber design	82
4.4	Summary	85
5	Regeneration strategy under reverse-flow operation	87
5.1	Experimental setup	87
5.2	Experimental procedure	92
5.2.1	Start-up procedure	93
5.2.2	Periodic operation	93
5.3	Experimental results	96
5.3.1	Performance indicators	96
5.3.2	RFR behaviour characteristics	97
5.3.3	Operability and robustness of operation	103
5.4	Summary	112
6	Modelling the RFR	113
6.1	Mathematical model	113
6.1.1	Packed bed	113
6.1.2	Combustion chamber	118
6.2	Numerical solution	120
6.2.1	Model implementation	121
6.2.2	Simulation control	122
6.3	Performance indicators	123
7	Simulation study	127
7.1	Asymmetric operation	127
7.1.1	Convective heat flux disproportion	127
7.1.2	Adjustment of operation parameters	130

7.2	Alternative reactor configurations for asymmetric operation	135
7.3	Symmetric operation	141
7.3.1	Simulation results	143
7.4	Summary and outlook	146
A	Complementary information and experimental parameter sets	151
A.1	Combustion chamber design	151
A.1.1	Experimental studies	151
A.1.2	Temperature distribution in the chamber	153
A.1.3	Simulation studies	154
A.1.4	Flow rate variation and effect on the real factor	154
A.2	Reverse flow operation	157
B	Technical drawings	159
B.1	Elements of the combustion chamber	159
B.2	Elements of the single chamber reactors	160
B.3	Reverse-flow reformer	161
C	Model parameters and physical properties	165
C.1	Model and simulation parameters set	165
C.1.1	Geometric dependant parameters	165
C.1.2	Physical and thermodynamic data of the bulk phases	166
C.1.3	Transport properties	168
C.1.4	Simulation parameters set	169
C.1.5	Derivation of the combustion chamber control strategy	170
D	Parametric studies based on simulation	175
D.1	Asymmetric operation	175
D.1.1	Operation parameters	175
D.1.2	Structure of the packed bed	179
D.2	Symmetric operation	181
E	Decentralized hydrogen production facility with RFR	185
E.1	Process description	185
E.2	Relevant process parameters	188