

Content

| | |
|---|-----------|
| <i>Acknowledgement</i> | I |
| <i>Contents</i> | III |
| <i>Abstract (English)</i> | XI |
| <i>Abbreviations</i> | XV |
| 1 Introduction | 1 |
| 1.1 <i>Motivations of the research</i> | 1 |
| 1.1.1 <i>Energy crisis and climate change</i> | 1 |
| 1.1.1.1 <i>BEE and energy crisis</i> | 1 |
| 1.1.1.2 <i>BEE and CER</i> | 2 |
| 1.1.2 <i>The necessity of energy retrofit in Cfa zone</i> | 2 |
| 1.1.3 <i>The dilemmas of BEE in Cfa zone</i> | 3 |
| 1.1.3.1 <i>The characteristics of building energy consumption in Cfa zone</i> | 4 |
| 1.1.3.2 <i>The technical barriers of BEE in Cfa zone</i> | 5 |
| 1.1.3.3 <i>The legal barriers of BEE in Cfa zone</i> | 6 |
| 1.1.4 <i>The dilemmas of housing retrofit in Cfa zone</i> | 7 |
| 1.2 <i>Area of the research</i> | 9 |
| 1.2.1 <i>Energy retrofit</i> | 9 |
| 1.2.2 <i>The Cfa zone</i> | 10 |
| 1.2.3 <i>Laws and standards</i> | 12 |
| 1.2.3.1 <i>Local standards</i> | 12 |
| 1.2.3.2 <i>The Passive House in Cfa zone</i> | 13 |
| 1.3 <i>Objectives of the research</i> | 14 |
| 1.4 <i>Methodology and structure</i> | 14 |
| 2 Status quo: energy consumption and standards..... | 17 |
| 2.1 <i>Introduction</i> | 17 |
| 2.1.1 <i>The energy standards</i> | 17 |

| | | |
|----------|---|----|
| 2.1.2 | <i>The analysis of the existing buildings.....</i> | 18 |
| 2.2 | <i>Existing buildings in Shanghai</i> | 18 |
| 2.2.1 | <i>The urban housing</i> | 20 |
| 2.2.2 | <i>The countryside housing</i> | 21 |
| 2.3 | <i>The energy consumptions of existing buildings computed by program in Shanghai.....</i> | 22 |
| 2.3.1 | <i>House A: The low-rise apartment</i> | 22 |
| 2.3.1.1 | <i>The existing condition</i> | 23 |
| 2.3.1.2 | <i>Heating and cooling demands by computer program.....</i> | 24 |
| 2.3.2 | <i>House B: The high-rise apartment</i> | 25 |
| 2.3.2.1. | <i>The existing condition</i> | 26 |
| 2.3.2.2. | <i>Heating and cooling demands by computer program.....</i> | 26 |
| 2.3.3 | <i>House C: Single family house in countryside.....</i> | 27 |
| 2.3.3.1 | <i>The existing condition</i> | 27 |
| 2.3.3.2 | <i>Heating and cooling demands by computer program.....</i> | 28 |
| 2.4 | <i>The climate and the comfort design.....</i> | 29 |
| 2.4.1 | <i>The climate data.....</i> | 29 |
| 2.4.2 | <i>The comfort zone.....</i> | 31 |
| 2.4.3 | <i>The psychometric analysis</i> | 32 |
| 2.5 | <i>Contents of current energy standards in Cfa zone.....</i> | 35 |
| 2.5.1 | <i>JGJ 134-2001.....</i> | 35 |
| 2.5.2 | <i>JGJ 134-2010.....</i> | 37 |
| 2.5.3 | <i>DGJ 08-205-2011.....</i> | 38 |
| 2.6 | <i>Passive House standard.....</i> | 38 |
| 2.6.1 | <i>Hamburger Pavilion.....</i> | 40 |
| 2.6.2 | <i>The Passive House Bruck.....</i> | 41 |
| 2.7 | <i>Summary.....</i> | 42 |
| 2.7.1 | <i>Targets of energy saving.....</i> | 42 |
| 2.7.2 | <i>The mechanism of the local BEE.....</i> | 43 |
| 2.7.3 | <i>The comparison between Passive House standard and local standards</i> | 44 |

| | |
|--|-----------|
| 3 Envelope: optimization and cost efficiency..... | 45 |
| 3.1 <i>Introduction</i> | 45 |
| 3.1.1 <i>Prototypes</i> | 46 |
| 3.1.1.1 <i>Constructions</i> | 46 |
| 3.1.1.2 <i>Energy consumption.....</i> | 48 |
| 3.1.2 <i>Efficiency of the incremental cost.....</i> | 51 |
| 3.2 <i>Insulation.....</i> | 52 |
| 3.2.1 <i>Insulation systems.....</i> | 52 |
| 3.2.1.1 <i>External insulation system</i> | 52 |
| 3.2.1.2 <i>Internal insulation system</i> | 53 |
| 3.2.2 <i>The problems of insulation systems.....</i> | 54 |
| 3.2.2.1 <i>The inside condensation in the internal insulation.....</i> | 54 |
| 3.2.2.2 <i>Rendering problem in EIFS system</i> | 55 |
| 3.2.2.3 <i>Thermal bridge.....</i> | 56 |
| 3.2.2.4 <i>Thermal break.....</i> | 57 |
| 3.2.3 <i>Simulations and comparison of insulation on the wall.....</i> | 59 |
| 3.2.4 <i>Insulation on the roof.....</i> | 61 |
| 3.2.4.1 <i>The warm roof.....</i> | 62 |
| 3.2.4.2 <i>The cold roof.....</i> | 63 |
| 3.2.5 <i>Simulations and comparison of insulation on the roof.....</i> | 63 |
| 3.3 <i>Windows.....</i> | 65 |
| 3.3.1 <i>Solar gain and the selective glazings</i> | 67 |
| 3.3.1.1 <i>Tinted glass</i> | 67 |
| 3.3.1.2 <i>Reflective glass.....</i> | 68 |
| 3.3.1.3 <i>Low-E glass.....</i> | 68 |
| 3.3.2 <i>Heat loss and insulated glazing unit</i> | 69 |
| 3.3.2.1 <i>Double glazing</i> | 70 |
| 3.3.2.2 <i>Insulated glazing unit with selective film</i> | 70 |
| 3.3.3 <i>Simulations and comparison of the different glazings.....</i> | 71 |
| 3.3.4 <i>The frame categories.....</i> | 73 |

| | | |
|----------|--|-----------|
| 3.3.5 | <i>Simulations and comparison of the different frames</i> | 74 |
| 3.4 | <i>Shading.....</i> | 77 |
| 3.4.1 | <i>Fixed shadings</i> | 78 |
| 3.4.2 | <i>Simulations of overhangs as the fixed shadings</i> | 78 |
| 3.4.3 | <i>Movable shadings</i> | 81 |
| 3.4.4 | <i>Simulations of rollers as the moveable shadings.....</i> | 83 |
| 3.4.5 | <i>The comparisons between reflective glazings and movable shadings ...</i> | 84 |
| 3.4.5.1 | <i>Reflective glazings compared with single clear glazings plus movable rollers.....</i> | 85 |
| 3.4.5.2 | <i>Reflective glazings compared with low-E glazings plus movable rollers</i> | 86 |
| 3.5 | <i>Evaporative cooling.....</i> | 87 |
| 3.5.1 | <i>Green roof.....</i> | 88 |
| 3.5.2 | <i>Green façade.....</i> | 89 |
| 3.6 | <i>Cost efficiency of incremental cost by the specific method</i> | 90 |
| 3.6.1 | <i>Type (a)</i> | 91 |
| 3.6.2 | <i>Type (b)</i> | 92 |
| 3.6.3 | <i>Type (c).....</i> | 92 |
| 3.6.4 | <i>Type (d)</i> | 93 |
| 3.6.5 | <i>Comparison.....</i> | 94 |
| 3.7 | <i>Summary.....</i> | 94 |
| 3.7.1 | <i>Energy efficiency.....</i> | 94 |
| 3.7.2 | <i>Cost efficiency.....</i> | 95 |
| 4 | Retrofit: 50%, 65% and Passive Houses..... | 97 |
| 4.1 | <i>Introduction</i> | 97 |
| 4.1.1 | <i>The design of 50%, 65% House</i> | 97 |
| 4.1.2 | <i>The design of Passive House.....</i> | 98 |
| 4.1.3 | <i>The investment costs of the retrofits</i> | 99 |
| 4.2 | <i>Retrofit of House A</i> | 100 |
| 4.2.1 | <i>Analysis and retrofit</i> | 100 |

| | | |
|---------|--|-----|
| 4.2.2 | <i>Retrofit according to the 50% energy saving (JGJ 134-2001)</i> | 101 |
| 4.2.2.1 | <i>Method of Provision.....</i> | 101 |
| 4.2.2.2 | <i>Method of Performance.....</i> | 102 |
| 4.2.3 | <i>Retrofit according to the 65% energy saving.....</i> | 103 |
| 4.2.3.1 | <i>Method of Provision.....</i> | 103 |
| 4.2.3.2 | <i>Method of Performance.....</i> | 104 |
| 4.2.4 | <i>Retrofit according to Passive House standard</i> | 105 |
| 4.2.4.1 | <i>Retrofit according to the technologies in the Bruck house</i> | 105 |
| 4.2.4.2 | <i>Option 1 (combination of double reflective glazing and clear glazing)</i> | 106 |
| 4.2.4.3 | <i>Option 2 (triple low-E glazing units)</i> | 107 |
| 4.2.4.4 | <i>Option 3 (double reflective glazing units).....</i> | 107 |
| 4.2.4.5 | <i>Comparison and discussion of the four options</i> | 108 |
| 4.2.5 | <i>Summary of House A.....</i> | 109 |
| 4.3 | <i>Retrofit of House B</i> | 111 |
| 4.3.1 | <i>Analysis and retrofit</i> | 111 |
| 4.3.2 | <i>Retrofit according to the 50% energy saving.....</i> | 112 |
| 4.3.2.1 | <i>Method of Provision.....</i> | 112 |
| 4.3.2.2 | <i>Method of Performance.....</i> | 112 |
| 4.3.3 | <i>Retrofit according to the 65% energy saving.....</i> | 113 |
| 4.3.3.1 | <i>Method of Provision.....</i> | 113 |
| 4.3.3.2 | <i>Method of Performance.....</i> | 114 |
| 4.3.4 | <i>Retrofit according to Passive House standard</i> | 115 |
| 4.3.4.1 | <i>Retrofit according to the technologies in the Bruck house</i> | 115 |
| 4.3.4.2 | <i>Option 1 (combination of various glazing products).....</i> | 116 |
| 4.3.4.3 | <i>Option 2 (triple insulated low-E glazing units).....</i> | 117 |
| 4.3.4.4 | <i>Option 3 (double insulated reflective glazing units).....</i> | 118 |
| 4.3.4.5 | <i>Comparison and discussion of the four options</i> | 118 |
| 4.3.5 | <i>Summary of House B.....</i> | 119 |
| 4.4 | <i>Retrofit of House C</i> | 121 |
| 4.4.1 | <i>Analysis and retrofit</i> | 121 |

| | | |
|----------------|---|-----|
| <i>4.4.2</i> | <i>Retrofit according to the 50% energy saving.....</i> | 122 |
| <i>4.4.2.1</i> | <i>Method of Provision.....</i> | 122 |
| <i>4.4.2.2</i> | <i>Method of Performance.....</i> | 123 |
| <i>4.4.3</i> | <i>Retrofit according to the 65% energy saving.....</i> | 123 |
| <i>4.4.3.1</i> | <i>Method of Provision.....</i> | 123 |
| <i>4.4.3.2</i> | <i>Method of Performance.....</i> | 124 |
| <i>4.4.4</i> | <i>Retrofit according to Passive House standard</i> | 125 |
| <i>4.4.4.1</i> | <i>Retrofit according to the technologies in the Bruck house</i> | 125 |
| <i>4.4.4.2</i> | <i>Option 1 (combinatioin of double reflective glazings and double low-E glazings).....</i> | 126 |
| <i>4.4.4.3</i> | <i>Option 2 (triple insulated glazing units)</i> | 127 |
| <i>4.4.4.4</i> | <i>Option 3 (double insulated reflective glazing)</i> | 128 |
| <i>4.4.4.5</i> | <i>Comparison and discussion of the four options</i> | 128 |
| <i>4.4.5</i> | <i>Summary of House C.....</i> | 129 |
| <i>4.5</i> | <i>Summary.....</i> | 131 |
| <i>4.5.1</i> | <i>The ambiguity feature of the local standards</i> | 131 |
| <i>4.5.2</i> | <i>Envelope properties.....</i> | 131 |
| <i>4.5.3</i> | <i>Investment costs</i> | 132 |
| 5 | Analysis: HVAC system and economy evaluation..... | 135 |
| <i>5.1</i> | <i>Introduction</i> | 135 |
| <i>5.1.1</i> | <i>Coal equivalent in China</i> | 136 |
| <i>5.1.2</i> | <i>Energy price</i> | 136 |
| <i>5.1.3</i> | <i>Economy evaluation.....</i> | 137 |
| <i>5.1.3.1</i> | <i>The overall cost.....</i> | 137 |
| <i>5.1.3.2</i> | <i>The net present value (NPV)</i> | 138 |
| <i>5.1.3.3</i> | <i>The efficiency of investment cost.....</i> | 139 |
| <i>5.2</i> | <i>HVAC system</i> | 141 |
| <i>5.2.1</i> | <i>Ventilation</i> | 141 |
| <i>5.2.1.1</i> | <i>Heat energy recovery system.....</i> | 142 |
| <i>5.2.1.2</i> | <i>Subsoil heat exchanger</i> | 143 |

| | | |
|----------------|--|-----|
| 5.2.2 | <i>Heat pump</i> | 143 |
| 5.2.2.1 | <i>Split heat pump</i> | 144 |
| 5.2.2.2 | <i>Compact heat pump</i> | 145 |
| 5.2.3 | <i>Evaporative cooler</i> | 146 |
| 5.2.4 | <i>Distribution and terminal units</i> | 147 |
| 5.2.4.1 | <i>Water system</i> | 147 |
| 5.2.4.2 | <i>Air system</i> | 148 |
| 5.2.5 | <i>Technical systems in 50% and 65% Houses</i> | 148 |
| 5.2.6 | <i>Technical systems in Passive Houses</i> | 149 |
| 5.3 | <i>Analysis of House A</i> | 153 |
| 5.3.1 | <i>The overall costs of House A</i> | 153 |
| 5.3.2 | <i>NPVs of House A</i> | 155 |
| 5.4 | <i>Analysis of House B</i> | 157 |
| 5.4.1 | <i>The overall costs of House B</i> | 158 |
| 5.4.2 | <i>NPVs of House B</i> | 159 |
| 5.5 | <i>Analysis of House C</i> | 162 |
| 5.5.1 | <i>The overall costs of House C</i> | 162 |
| 5.5.2 | <i>NPVs of House C</i> | 164 |
| 5.6 | <i>The capability of CER</i> | 166 |
| 5.6.1 | <i>The CER capability by the individual building</i> | 166 |
| 5.6.2 | <i>The cost of the CER capability</i> | 167 |
| 5.6.3 | <i>The CER capability by the given budget</i> | 167 |
| 5.7 | <i>Summary</i> | 169 |
| 5.7.1 | <i>Indicator of primary energy</i> | 169 |
| 5.7.2 | <i>HVAC system</i> | 169 |
| 5.7.3 | <i>Cost efficiency</i> | 170 |
| 5.7.3.1 | <i>Cost efficiency by life-cycle analysis</i> | 170 |
| 5.7.3.2 | <i>Cost efficiency of the investment</i> | 171 |
| 6 | Conclusions and discussions | 173 |

| | | |
|------------|--|-----|
| 6.1 | <i>The challenge from indoor comfort.....</i> | 173 |
| 6.1.1 | <i>The features of local BEE.....</i> | 174 |
| 6.1.2 | <i>Retrofit to the 50%, 65%, and Passive Houses in Cfa zone.....</i> | 174 |
| 6.1.2.1 | <i>Envelope retrofit methods.....</i> | 175 |
| 6.1.2.2 | <i>HVAC system.....</i> | 176 |
| 6.1.3 | <i>The electricity consumed by the three Passive Houses.....</i> | 177 |
| 6.1.4 | <i>Life-cycle analysis.....</i> | 178 |
| 6.1.4.1 | <i>Overall cost throughout 30 years.....</i> | 178 |
| 6.1.4.2 | <i>NPVs</i> | 178 |
| 6.2 | <i>The challenge from CER.....</i> | 179 |
| 6.2.1 | <i>The challenge for the financial support.....</i> | 179 |
| 6.2.2 | <i>The CER capability of the investments.....</i> | 180 |
| 6.3 | <i>The reasonability of Passive House standard in Cfa zone</i> | 181 |
| 6.4 | <i>Further research questions</i> | 181 |
| 6.4.1 | <i>Passive House in China's other climate zones</i> | 182 |
| 6.4.2 | <i>The new constructions of Passive House in China.....</i> | 182 |
| 7 | Bibliography..... | 185 |
| 7 | Appendix | 197 |
| 7.1 | <i>The baseline building in Cfa zone.....</i> | 197 |
| 7.2 | <i>Provisions of envelope elements</i> | 198 |
| 7.2.1 | <i>Provisions of envelope elements stipulated in JGJ 134-2001.....</i> | 198 |
| 7.2.2 | <i>Provisions of envelope elements stipulated in JGJ 134-2010.....</i> | 199 |
| 7.2.3 | <i>Provisions of envelope elements stipulated in DGJ 08-205-2011</i> | 202 |
| 7.3 | <i>Net present values of the designs</i> | 204 |
| 7.3.1 | <i>NPVs of House A.....</i> | 204 |
| 7.3.2 | <i>NPVs of House B.....</i> | 209 |
| 7.3.3 | <i>NPVs of House C.....</i> | 213 |
| 7.4 | <i>List of Figures.....</i> | 218 |
| 7.5 | <i>List of Tables.....</i> | 224 |