

Table of contents

Nomenclature	V
Abstract	XI
Kurzfassung	XV
Chapter 1 Introduction	1
1.1 Motivation	1
1.2 Objectives.	4
1.3 Research tasks and thesis outline	5
Chapter 2 State of research and technology	7
2.1 Indoor air flow	7
2.2 Multicomponents	8
2.3 Comparison of simulation results of different CFD programs	11
2.4 Contribution of the present work	12
Chapter 3 Numerical Modeling	15
3.1 CAD modeling and meshing	16
3.1.1 Base case model	16
3.1.2 3D Test room	17
3.2 Governing equations	19
3.2.1 Laminar flow	19
3.2.2 Turbulent flow.	20
3.3 Boundary conditions	23
3.4 Model parameters	25
3.5 Double configuration	25

Table of contents

3.6	CFD procedure	26
3.7	Codes used in this work	27
3.7.1	CFX	28
3.7.2	FLUENT	29
3.7.3	OpenFOAM	29
3.8	Concluding remarks	29
Chapter 4	Base case simulation results.	31
4.1	Indoor air flow model	31
4.1.1	Turbulent flow	34
4.1.2	Laminar flow	39
4.1.3	Conclusion	39
4.2	Indoor air flow model with an emission source	39
4.2.1	Turbulent flow	42
4.2.2	Laminar flow	47
4.2.3	Conclusion	47
4.3	Pollutants distribution model based on double configuration	47
4.3.1	Two components system	48
4.3.2	Three components system	50
4.4	Concluding remarks	52
Chapter 5	Experimental investigation	55
5.1	Test setup	55
5.2	Measurement technique	58
5.3	Experimental procedure and conditions	58
5.4	Measurement results and discussion	62
5.4.1	Two components system (without flow obstruction)	63
5.4.2	Two components system (with flow obstruction)	67
5.4.3	Three components system	69
5.4.4	Further experiments	75

5.5	Concluding remarks	76
Chapter 6	Comparison of simulation results with experimental results	79
6.1	Indoor air flow model	79
6.2	Developed simulation model based on double configuration	81
6.2.1	Two components system (without flow obstruction)	81
6.2.2	Two components system (with flow obstruction)	86
6.2.3	Three components system	87
6.3	Concluding remarks	91
Chapter 7	Further simulation studies	93
7.1	Case 1 – Influence of air change rate	93
7.2	Case 2 – Influence of different initial in-room pollutant concentrations	98
7.3	Case 3 – Influence of different pollutant inlet flowrates	99
7.4	Case 4 – Influence of different air inlet flowrates with the same pollutant inlet flowrate	101
7.5	Case 5 – Influence of different time durations of pollutant inlet	104
7.6	Concluding remarks	105
Chapter 8	Summary and outlook.	107
8.1	Summary	107
8.2	Outlook	111
Appendix A	Experimental	113
A.1	Measurement technique	114
A.1.1	Flame ionization detector	114
A.1.2	Infrared photometer	116
A.1.3	Wilson flow grid	117
A.2	Weight analysis of propane cylinder	119
A.3	Further experiments	121
A.3.1	Two components system (without flow obstruction)	121
A.3.2	Two components system (with flow obstruction)	122

Table of contents

Appendix B	Simulation	131
B.1	2D base case model	132
B.1.1	Laminar indoor air flow model	132
B.1.2	Laminar indoor air flow model with an emission source	136
B.1.3	OpenFOAM running in parallel on computing cluster	141
B.2	Developed simulation model based on double configuration	144
B.2.1	Time dependent expression for the mass source contribution	144
B.2.2	Influence of diffusion	145
B.2.3	Comparison of simulation results with experimental results.	147
References		151