

# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Motivation . . . . .	1
1.2	Objectives of the thesis . . . . .	5
1.3	Contributions of the thesis . . . . .	6
1.3.1	Network-controlled sidelink communication to of-fload network traffic . . . . .	7
1.3.2	Applying network-controlled sidelink communica-tion in the mMTC use case . . . . .	7
1.3.3	Network-controlled V2X communication . . . . .	8
1.3.4	Performance evaluation of D2D and V2X commu-nications . . . . .	8
1.4	Relevant publications . . . . .	9
1.5	Organization of the thesis . . . . .	9
<b>2</b>	<b>Evaluation Framework and Methodology</b>	<b>13</b>
2.1	Evaluation methodology for 4G . . . . .	13
2.1.1	Analysis-based and inspection-based KPI evalua-tion	13
2.1.2	Simulation-based KPI evaluation . . . . .	14
2.2	Evaluation of beyond 4G technologies and capabilities . .	16
2.3	Simulation guidelines for this thesis . . . . .	18
2.3.1	KPIs and their evaluation . . . . .	18
2.3.2	Deployment scenarios . . . . .	19
2.3.2.1	Synthetic deployment scenario . . . . .	20
2.3.2.2	Realistic deployment scenario . . . . .	20
2.3.3	Channel models . . . . .	21
2.3.3.1	Pathloss models for synthetic scenarios .	22
2.3.3.2	3D channel models for realistic scenarios	25
2.3.4	Mobility models . . . . .	31

2.3.5	Traffic models . . . . .	32
2.3.6	UE power consumption model . . . . .	32
2.3.7	Simulation procedure and flow . . . . .	32
2.4	Summary . . . . .	36
<b>3</b>	<b>Context-aware Network-controlled Sidelink Communications to Offload Network Traffic</b>	<b>39</b>
3.1	Introduction . . . . .	39
3.2	System capacity optimization for D2D underlay operation	41
3.2.1	System Model . . . . .	41
3.2.2	Maximize the number of D2D links . . . . .	44
3.2.2.1	Construction of the optimization problem	44
3.2.2.2	Heuristic RRM algorithm . . . . .	46
3.2.2.3	Effectiveness of the algorithm . . . . .	49
3.2.3	System capacity maximization . . . . .	51
3.2.4	Simulation parameters and numerical results . . .	56
3.3	Dynamic context-aware optimization of D2D w.r.t. user satisfaction . . . . .	60
3.3.1	System model . . . . .	60
3.3.2	Construction of the optimization problem . . . . .	62
3.3.3	Heuristic RRM algorithm . . . . .	64
3.3.4	Extension of the RRM algorithm: taking account of the UE priority information . . . . .	68
3.3.5	Evaluation and numerical results . . . . .	70
3.4	Radio link enabler for context-aware D2D in the reuse mode	73
3.4.1	Challenges and the proposed solution . . . . .	73
3.4.2	Signaling scheme in single-cell . . . . .	75
3.4.3	Signaling scheme in multi-cells . . . . .	77
3.4.4	Simulation assumptions and numerical results . .	79
3.5	Summary . . . . .	84

<b>4 Applying Network-controlled Sidelink Communication in the mMTC Use Case</b>	<b>87</b>
4.1 Introduction . . . . .	87
4.2 System model . . . . .	90
4.3 Device clustering and transmission mode selection . . . . .	91
4.3.1 Clustering of mMTC devices . . . . .	91
4.3.1.1 Clustering in a rural area . . . . .	92
4.3.1.2 Clustering in a dense urban scenario . . . . .	93
4.3.1.3 A brief summary of the different approaches	95
4.3.2 TM selection . . . . .	96
4.4 Design of signaling procedures . . . . .	100
4.4.1 Initial attachment of a sensor . . . . .	100
4.4.2 TM update procedure . . . . .	102
4.4.3 Uplink reports by sidelink communication . . . . .	104
4.5 Evaluation and numerical results . . . . .	106
4.6 Summary . . . . .	114
<b>5 Network-controlled V2X Communication</b>	<b>115</b>
5.1 Introduction . . . . .	115
5.2 Cellular V2X communication through network infrastructures . . . . .	117
5.2.1 System model and evaluation methodology . . . . .	117
5.2.1.1 Uplink latency . . . . .	119
5.2.1.2 Propagation latency between BSs . . . . .	121
5.2.1.3 Downlink latency . . . . .	122
5.2.2 Numerical results . . . . .	125
5.3 Direct V2X communication via the PC5 interface . . . . .	128
5.4 Two-hop V2X communication over sidelink . . . . .	132
5.4.1 System model of two-hop direct V2X communication	133
5.4.2 Context-aware radio resource management . . . . .	135

5.4.3	Transmission range maximization for two-hop V2X communication . . . . .	136
5.4.3.1	Optimization problem . . . . .	136
5.4.3.2	Radio resource allocation between the two different hops . . . . .	139
5.4.4	Simulation parameters and numerical results . . .	140
5.5	Applying multi-RAT to enhance the reliability of V2X communication . . . . .	144
5.5.1	Multi-RAT V2X communication . . . . .	145
5.5.1.1	Independent transmissions over the LTE-Uu and the PC5 . . . . .	145
5.5.1.2	Coordinated transmissions over the LTE-Uu and the PC5 . . . . .	148
5.5.2	Hybrid uplink . . . . .	150
5.5.2.1	Hybrid uplink procedure: exploiting the transmission over the PC5 interface . . .	150
5.5.2.2	Hybrid uplink: multi-RAT to improve uplink reliability . . . . .	153
5.5.2.3	Coordination between different RATs in hybrid uplink . . . . .	154
5.5.3	Fast MBSFN area mapping . . . . .	159
5.5.4	Simulation parameters and numerical results . . .	162
5.6	Summary . . . . .	170
<b>6</b>	<b>Conclusion</b>	<b>173</b>
6.1	Summary . . . . .	173
6.2	Future work . . . . .	176